

# P3CD08065B

650V/8A SiC Power Schottky Barrier Diode Product



**POWERCUBESEMI, INC.**

Potential · Convergence · Smart

## Features

- Positive temperature coefficient for easy parallel use
- Switching characteristics that are not affected by temperature
- Maximum operating temperature 175 °C
- Zero reverse recovery current
- Zero forward recovery voltage

## Benefits


- Unipolar device
- Greatly reduce switching losses
- No thermal crash in parallel devices
- Reduce system dependence on heat sinks

## Applications

- Switch Mode Power Supply (SMPS), Power Factor Correction (PFC)
- Motor drive, photovoltaic inverter, uninterruptible power supply, Wind turbines, train traction systems, electric vehicles.

Key Characteristics		
$V_{RRM}$	650	V
$I_F, T_C \leq 150^\circ\text{C}$	4*	A
$Q_C$	11*	nC

\* : per Leg



PKG : TO-247



A(1) C(2) A(3)



## Absolute Maximum Ratings $T_C = 25^\circ\text{C}$ unless otherwise specified

Symbol	Parameter	Test Condition	Value	Unit
$V_{RRM}$	Repetitive Peak Reverse Voltage		650	V
$V_{RSM}$	Surge Peak Reverse Voltage		650	V
$V_{DC}$	DC Blocking Voltage		650	V
$I_F$	Continuous Forward Current	$T_C=25^\circ\text{C}$	11*	A
		$T_C=135^\circ\text{C}$	5*	A
		$T_C=150^\circ\text{C}$	4*	A
$I_{FRM}$	Repetitive Peak Forward Surge Current	$T_C=25^\circ\text{C}$ , $t_p=10\text{ms}$ , Half Sine Wave, $D=0.3$	15*	A
$I_{FSM}$	Non-repetitive Peak Forward Surge Current	$T_C=25^\circ\text{C}$ , $t_p=10\text{ms}$ , Half Sine Wave	35*	A
$P_{TOT}$	Power Dissipation	$T_C=25^\circ\text{C}$	53.2*	W
		$T_C=110^\circ\text{C}$	23*	
$T_j$	Operating Junction		-55 to 175	$^\circ\text{C}$
$T_{stg}$	Storage Temperature		-55 to 175	$^\circ\text{C}$



### Thermal Characteristics


Symbol	Parameter	Test Condition	Value	Unit
			Typ.	
$R_{thJc}$	Thermal resistance from junction to case		2.82* 1.41**	°C/W

### Electrical Characteristics, Nomination temperature $T_j=25^{\circ}\text{C}$


Symbol	Parameter	Test Condition	Numerical		Unit
			Typ.	Max.	
$V_F$	Forward Voltage	$I_F=4\text{A}, T_j=25^{\circ}\text{C}$	1.57	1.7	V
		$I_F=4\text{A}, T_j=175^{\circ}\text{C}$	1.8	2.5	
$I_R$	Reverse Current	$V_R=650\text{V}, T_j=25^{\circ}\text{C}$	10	50	$\mu\text{A}$
		$V_R=650\text{V}, T_j=175^{\circ}\text{C}$	20	100	
$Q_C$	Total capacitive Charge	$V_R=400\text{V}, T_j=150^{\circ}\text{C}$ $Q_C = \int_0^{V_R} C(V) dV$	11	-	nC
C	Total Capacitance	$V_R=0\text{V}, T_j=25^{\circ}\text{C}, f=1\text{MHZ}$	181	220	pF
		$V_R=200\text{V}, T_j=25^{\circ}\text{C}, f=1\text{MHZ}$	22.5	25	
		$V_R=400\text{V}, T_j=25^{\circ}\text{C}, f=1\text{MHZ}$	20.5	21	

## Performance Graphs


1) Forward IV characteristics as a function of  $T_j$




2) Reverse IV characteristics as a function of  $T_j$




3) Current Derating



4) Capacitance VS. reverse voltage



### Package Outline



SYMBOL	DIMENSIONS			NOTES
	MIN	NOM	MAX	
<b>A</b>	4.83	5.02	5.21	
<b>A1</b>	2.29	2.41	2.55	
<b>A2</b>	1.50	2.00	2.49	
<b>b</b>	1.12	1.20	1.33	
<b>b1</b>	1.12	1.20	1.28	
<b>b2</b>	1.91	2.00	2.39	6
<b>b3</b>	1.91	2.00	2.34	
<b>b4</b>	2.87	3.00	3.22	6, 8
<b>b5</b>	2.87	3.00	3.18	
<b>c</b>	0.55	0.60	0.69	6
<b>c1</b>	0.55	6.00	0.65	
<b>D</b>	20.80	20.95	21.10	4
<b>D1</b>	16.25	16.55	17.65	5
<b>D2</b>	0.51	1.19	1.35	
<b>E</b>	15.75	15.94	16.13	4
<b>E1</b>	13.46	14.02	14.16	5
<b>E2</b>	4.32	4.91	5.49	3
<b>e</b>	5.44 BSC			
<b>L</b>	19.81	20.07	20.32	
<b>L1</b>	4.10	4.19	4.40	6
<b><math>\phi P</math></b>	3.56	3.61	3.65	7
<b><math>\phi P1</math></b>	7.19 REF			
<b>Q</b>	5.39	5.79	6.20	
<b>S</b>	6.04	6.17	6.30	

Symbol	Parameter	Test Condition	Numerical		Unit
			Typ.	Max.	
$M_d$	Mounting torque	M3 Screw 6-32 Screw	1/8.8	-	Nm/ lbf.in.