

PM004P060AG




-60V -160A 4.5mΩ Si Single P-ch Enhancement Mode MOSFET with Normal Diode

Features

Si P-Ch Enhancement Mode Power MOSFET


- Rated to -60V at -160Amps @ $T_J = 25^\circ\text{C}$
- Max $R_{DS(\text{on})} = 4.5 \text{ m}\Omega$
- Typ $R_{DS(\text{on})} = 3.7 \text{ m}\Omega$
- Gate Charge(Typ. $Q_g=305 \text{ nC}$)
- 100% Avalanche Tested



PKG type : TO-220

Application

- Power switch
- DC/DC converters



Description

The PM004P060AG uses advanced trench technology to provide excellent $R_{DS(\text{ON})}$, low gate charge. It can be used in a wide variety of applications.

Absolute Maximum Ratings

Symbol	Parameter	Test Condition	Value	Unit
BV_{DSS}	Drain-source breakdown Voltage	$V_{GS}=0\text{V}$, $I_D=-250\mu\text{A}$	-60	V
I_D	Drain current	$T_c=25^\circ\text{C}$	-160	A
I_{DM}	Drain current	Pulse width limited by junction temperature	-640	A
V_{GS}	Gate-source voltage		± 20	V
E_{AS}	Single pulsed avalanche energy	$V_{GS}=-10\text{V}$, $R_G=25\Omega$ $V_{DD}=-50\text{V}$, $L=0.5\text{mH}$	900	mJ
P_d	Power dissipation	$T_c=25^\circ\text{C}$	280	W
T_j	Operating junction		150	°C
T_{stg}	Storage temperature		-55 to 150	°C



Package Marking and Ordering Information

Device Marking	Device	Package	Packing Method	Tape width	Quantity
PM004P060AG	PM004P060	TO-220	TUBE	-	50

Electrical Characteristics of Si MOSFET

Symbol	Parameter	Test Condition	Numerical			Unit
			Min	Typ.	Max.	
BV_{DSS}	Drain-source breakdown voltage	$V_{GS} = 0V, I_D = -250\mu A, T_J = 25^\circ C$	-60	-	-	V
I_{DSS}	Zero gate voltage drain current	$V_{DS} = -60V, V_{GS} = 0V$	-	-	-1	μA
I_{GSS}	Gate-source leakage current	$V_{GS} = \pm 20V$	-	-	± 100	nA
$V_{GS(th)}$	Gate threshold voltage	$V_{DS} = V_{GS}, I_D = -250\mu A$	-1.3	-2.3	-2.5	V
$R_{DS(ON)}$	Static drain-source on state resistance	$V_{GS} = -10V, I_D = -15A$	-	3.7	4.5	mΩ
		$V_{GS} = -4.5V, I_D = -15A$	-	5.5	7.0	
g_{FS}	Forward transconductance	$V_{DS} = -5V, I_D = -15A$	-	42	-	S
$t_{d(on)}$	Turn-on Delay time	$V_{DD} = -30V, I_D = -15A, R_G = 1.6\Omega$	-	24	-	ns
t_r	Turn-on Rise time		-	36	-	
$t_{d(off)}$	Turn-off Delay time		-	301	-	
t_f	Turn-off Fall time		-	80	-	



Electrical Characteristics of Si MOSFET

Symbol	Parameter	Test Condition	Numerical		Unit
			Typ.	Max.	
$R_{\theta JC}$	Thermal resistance, Junction to case		0.45	-	°C/W
C_{iss}	Input capacitance	$V_{DS} = -30V, V_{GS} = 0V,$ $f = 1.0MHz$	9151	-	pF
C_{oss}	Output capacitance		1468	-	
C_{rss}	Reverse transfer capacitance		365	-	
$Q_{g(tot)}$	Total gate charge at 10V	$V_{DD} = -30V, I_D = -15A$ $V_{GS} = -10V$	305	-	nC
Q_{gs}	Gate to source gate charge		33	-	
Q_{gd}	Gate to drain "Miller" charge		82	-	

Electrical Characteristics of Si Diode

Symbol	Parameter	Test Condition	Numerical		Unit
			Typ.	Max.	
I_S	Maximum continuous drain to source diode forward current	$T_c=25^\circ C$	-	-160	A
V_{SD}	Drain to source diode forward voltage	$I_{SD} = -15A, V_{GS} = 0V$	-	-1.2	V
T_{rr}	Reverse recovery time	$I_F = -15A, V_{GS} = 0V,$ $dI_F/dt = -100A/\mu s$	95	-	ns
Q_{rr}	Reverse recovery charge		352	-	nC

Typical Characteristics




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Drain Source On Resistance




Figure 4. Gate Charge




Figure 5. Capacitance




Figure 6. Source-Drain Diode Forward

Typical Characteristics




Figure 7. Drain-Source On-Resistance




Figure 8. Safe Operation Area




Figure 9. Normalized Maximum Transient Thermal Impedance

Package Outline

Unit : mm

