

PTDH3065BY




POWERCUBESEMI, INC.
Potential · Convergence · Smart

650V 30A Si IGBT Discrete

Features

Si IGBT Discrete


- Rated to 650V at 30Amps @ $T_C=100^\circ\text{C}$
- $V_{CE(\text{sat})}=1.95\text{V}$ @ $I_C=30\text{A}$
- Low switching losses
- Maximum Junction Temperature 175°C
- Positive Temperature Coefficient
- High ruggedness, temperature stable
- High short circuit capability (5us)



PKG type : TO-247

Application

- High frequency switching application
- Medical applications
- Uninterruptible power supply
- Motion/Servo control



Absolute Maximum Ratings

Symbol	Parameter		Value	Unit
BV_{CES}	Collector-Emitter Breakdown Voltage		650	V
I_C	DC Collector Current	$T_C=25^\circ\text{C}$	60	A
		$T_C=100^\circ\text{C}$	30	
$I_{C,\text{Pulse}}$	Pulsed Collector Current		120	A
I_F	Diode Forward Current	$T_C=25^\circ\text{C}$	60	A
		$T_C=100^\circ\text{C}$	30	
$I_{F,\text{Pulse}}$	Diode Pulsed Current		120	A
V_{GE}	Continuous Gate-Emitter Voltage		± 20	V
V_{GE}	Transient Gate-Emitter Voltage		± 30	
P_D	Power Dissipation	$T_C=25^\circ\text{C}$	187	W
t_{SC}	Short circuit withstand time		5	μs
T_{vj}	Operating Junction Temperature Range		-40 to 175°C	$^\circ\text{C}$
T_{stg}	Storage Temperature Range		-55 to 150	



Package Marking and Ordering Information

Device Marking	Device	Package	Packing Method	Tape width	Quantity
PTDH3065BY	PTDH3065	TO-247	TUBE	-	30

Electrical Characteristics

$T_j=25^\circ\text{C}$ Unless Otherwise Specified

Static Characteristics

Symbol	Parameter	Test Condition	Numerical			Unit
			Min	Typ	Max	
BV_{CES}	Collector-Emitter Breakdown Voltage	$I_C=250\mu\text{A}, V_{\text{GE}}=0\text{V}$	650	-	-	V
$V_{\text{CE}(\text{sat})}$	Collector-Emitter Saturation Voltage	$I_C=30\text{A}, V_{\text{GE}}=15\text{V}$	$T_j=25^\circ\text{C}$	-	1.95	2.40
			$T_j=125^\circ\text{C}$	-	2.30	-
			$T_j=150^\circ\text{C}$	-	2.40	-
$V_{\text{GE}(\text{TH})}$	Gate-Emitter Threshold Voltage	$V_{\text{CE}}=V_{\text{GE}}, I_C=0.43\text{mA}$	4.1	5.1	6.1	V
I_{CES}	Zero Gate Voltage Collector Current	$V_{\text{CE}}=650\text{V}, V_{\text{GE}}=0\text{V}$	$T_j=25^\circ\text{C}$	-	-	0.25
			$T_j=150^\circ\text{C}$	-	-	4.00
I_{GES}	Gate-Emitter Leakage Current	$V_{\text{GE}}=\pm 20\text{V}, V_{\text{CE}}=0\text{V}$	-	-	100	nA

Dynamic Characteristics

Symbol	Parameter	Test Condition	Numerical			Unit
			Min	Typ	Max	
Q_G	Total Gate Charge	$V_{\text{CC}}=300\text{V}, I_C=30\text{A}, V_{\text{GE}}=15\text{V}$	-	0.15	-	uC
V_F	Diode Forward Voltage	$I_F=30\text{A}$	$T_j=25^\circ\text{C}$	-	1.90	2.60
			$T_j=125^\circ\text{C}$	-	1.85	-
			$T_j=150^\circ\text{C}$	-	1.75	-
C_{IES}	Input Capacitance	$V_{\text{CE}}=25\text{V}, V_{\text{GE}}=0\text{V}, f=1\text{MHz}$	-	1.16	-	nF
C_{RES}	Reverse Transfer Capacitance		-	0.05	-	
$I_{\text{C}(\text{SC})}$	Short circuit collector current	$V_{\text{GE}}=15\text{V}, t_{\text{SC}} \leq 5\mu\text{s}, V_{\text{CC}}=300\text{V}, T_j \leq 150^\circ\text{C}$	-	150	-	A



Electrical Characteristics

Switching Characteristics

Symbol	Parameter	Test Condition	Numerical			Unit				
			Min	Typ	Max					
$t_{d(on)}$	Turn-On Delay Time	$V_{GE}=0\sim15V$, $V_{CC}=400V$, $I_C=30A$, $R_G=10\Omega$, $L_s=60nH$	$T_j=25^\circ C$	-	8	-	ns			
				-	7	-				
				-	8	-				
	Turn-On Rise Time		$T_j=125^\circ C$	-	22	-				
				-	21	-				
				-	21	-				
	Turn-Off Delay Time		$T_j=150^\circ C$	-	80	-				
				-	86	-				
				-	90	-				
	Turn-Off Fall Time			-	84	-				
				-	112	-				
				-	135	-				
E_{on}	Turn-On Switching Energy			-	1.05	-	mJ			
				-	1.11	-				
				-	1.14	-				
	Turn-Off Switching Energy			-	0.49	-				
E_{off}	Reverse Recovery Energy			-	0.64	-	mJ			
				-	0.73	-				
				-	0.09	-				
E_{rec}	Reverse Recovery Energy			-	0.22	-	mJ			
				-	0.26	-				
				-	7	-				
I_{rr}	Reverse Recovery Current		$I_F=30A$, $V_R=400V$, $dI/dt=-350A/\mu s$	$T_j=25^\circ C$	-	13	A			
					-	15				
					-	0.14				
Q_{rr}	Reverse Recovery Charge				-	0.94	uC			
					-	1.26				
					-	42				
T_{rr}	Reverse Recovery Time				-	153	ns			
					-	161				
					-	-				

Thermal Characteristics

Symbol	Parameter	Numerical	Unit
$R_{\theta(J-A)}$	Thermal Resistance Junction-to-Ambient	40	K/W
$R_{\theta(J-C)}$	Thermal Resistance Junction-to-Case for IGBT	0.80	
$R_{\theta(J-C)}$	Thermal Resistance Junction-to-Case for Diode	1.4	

Typical Characteristics




Figure 1. Power dissipation as a function of case temperature ($T_J \leq 175^\circ\text{C}$)




Figure 2. Collector current as a function of case temperature ($V_{GE} \geq 15\text{V}$, $T_J \leq 175^\circ\text{C}$)




Figure 3. Output Characteristics ($T_J = 25^\circ\text{C}$)




Figure 4. Output Characteristics ($T_J = 150^\circ\text{C}$)

Typical Characteristics




Figure 5. Typical transfer characteristic
($V_{GE}=20V$)




Figure 6. Typical collector-emitter saturation voltage as a function of T_J ($V_{GE}=15V$)




Figure 7. Typical switching time as a function of collector current




Figure 8. Typical switching times as a function of gate resistance

Typical Characteristics




Figure 9. Typical switching times as a function of junction temperature




Figure 10. Gate to emitter threshold voltage as a function of junction temperature ($I_c=0.5\text{mA}$)




Figure 11. Typical switching energy losses as a function of collector current




Figure 12. Typical switching energy losses as a function of gate resistance

Typical Characteristics




Figure 13. Typical switching energy losses as a function of junction temperature




Figure 14. Typical switching energy losses as a function of collector to emitter voltage




Figure 15. Typical gate charge ($I_c=30A$)




Figure 16. Typical capacitance as a function of collector to emitter voltage

Typical Characteristics




Figure 17. IGBT Transient Thermal Impedance




Figure 18. Diode Transient Thermal Impedance




Figure 19. Diode forward current as a function of forward voltage





Figure 20. Typical diode forward voltage as a function of junction temperature



Package Outline



Unit : mm

SYMBOL	DIMENSIONS	
	MIN	MAX
A	4.80	5.20
A1	2.21	2.61
A2	1.85	2.15
b	1.0	1.4
b2	1.91	2.21
C	0.5	0.7
D	20.70	21.30
D1	16.25	16.85
E	15.50	16.10
E1	13.0	13.6
E2	4.80	5.20
E3	2.30	2.70
L	19.62	20.22
L1	-	4.30
ΦP	3.40	3.80
ΦP1	-	7.30
S	6.15 Typ	
H1	5.44 Typ	
b3	2.80	3.20